

STRONG ADHESIVE KRAFT PAPER TAPE

Reference	Colour	Message	Width in mm	Length in m	Inside of the chuck in mm	Outside of the chuck in mm
ADG12D2	Brown	-	50	50	76	130
ADG19D2	Brown	-	75	50	76	130
ADG12D2BG	Brown	Security tapes	50	50	76	130
ADG12D2FR	Brown	Fragile	50	50	76	130

TECHNICAL DATA

Support	70g/m ² kraft paper
Adhesive mass	Natural rubber
Total thickness in μ	115
Adhesive strength on steel in N/cm	1.7
Breaking load in N/cm	56
Elongation at break in %	6
Temperature resistance	60°C

APPLICATIONS / BENEFITS

Recommended for parcels up to 30 kg.

Aesthetic and efficient, it ensures a perfect and easy closing of your parcels. Good instant adhesion. Allows writing.

Reminder: your adhesive tape packages must not be opened with a sharp tool which could damage your rolls. A roll must be handled with care: a fall can create an invisible lesion which often causes the tape to break.

We recommend that you carry out tests under actual application conditions and ensure that the product selected meets your requirements in every respect.

For best results, we recommend that you apply your adhesive at a temperature above 10°C on a clean and dry surface.

Apply light pressure to your tape using the roller of your dispenser.

You can find all our adhesives and dispensers in our catalogue or on our website: www.raja.fr.

CONDITIONS OF STORAGE

We recommend that you store your adhesives in their original packaging. In the event of a complaint, you will be asked to return samples and to specify the information on the label of the cardboard box allowing the traceability of the product.

Adhesive tapes should be stored for a maximum of 6 months in a clean, dry place at a temperature of between 15 and 25°C and protected from UV light.

All our standard adhesives can be customised with your brand on www.Rajaprint.fr.