



DATENBLATT | datasheet

Tisch Lesegerät | Desktop Reader ARE DT2.0 LF

Elektrische Daten | electrical characteristics

Lesesystem reading systems	ASK, PSK, ISO fdx-b, ISO hdx, fdx-b Temperatur (kompatibler Transponder erforderlich) fdx-b temperature (compatible transponder required)
Betriebsfrequenz operational frequency	134.2 kHz, 125 kHz (opt.)
Schnittstelle interface	USB, HID
Stromversorgung power supply	5V via USB
Zusatzfunktion Features	Farb-LED Leuchtring, Signalton Color - LED ring, Buzzer
Stromaufnahme Input Current (typ.)	I=45mA (idle), I=130mA (typ.), I=160mA (max.)
Option	Oberflächenmontage Surface mounting version

Umweltbedingungen | environment

Lagertemperatur storage temperature	-25°C bis up to +60°C
Betriebstemperatur operating temperature	-25°C bis up to +60°C
Gehäuse Schutzklasse packaging protection class	IP 51
Schock&Vibration Shock&Vibration	IEC 68-2-6 / 29

Abmessungen | dimension

Gewicht weight	Ca. 50 g
Durchmesser diameter	110 mm
Höhe height	30 mm
Material material	ABS



AEG Identifikationssysteme GmbH

Hörvelsinger Weg 47, D-89081 Ulm | P: +49 (0)731 140088-0 | F: +49 (0)731 140088-9000

E-Mail: info@aegid.de | www.aegid.de

AEG is a registered trademark used under license from AB Electrolux (publ).