



DATENBLATT | datasheet

Kompakt Lesegerät | Compact Reader ARE i2.0x HF

Elektrische Daten | electrical characteristics

Lesesystem reading systems	ISO 15693
Betriebsfrequenz operational frequency	13.56 MHz
Schnittstelle interface	RS 232
Softwaresteuerung software control	Einfaches serielles ASCII Steuerprotokoll Easy serial ASCII based control protocol
Stromversorgung power supply	7V... 24V DC
Antennen antennae	Externe Luftspule external air core coil AAN- X1L HF, -X9L HF, AAN Xi9F HF

Umweltbedingungen | environment

Lagertemperatur storage temperature	-20°C bis up to +70°C
Betriebstemperatur operating temperature	-20°C bis up to +70°C
Gehäuse Schutzklasse packaging protection class	IP 65
Schock&Vibration Shock&Vibration	IEC 68-2-6 / 29

Befestigung | mounting option

	Hutschienemontage top hat rail mount
	2 Befestigungsstreben 2 mounting bracelets

Abmessungen | dimension

Gewicht weight	Ca. 170 g
Länge length	90 mm
Breite width	58 mm
Höhe height	38 mm
Material material	PA6, ABS



AEG Identifikationssysteme GmbH

Hörvelsinger Weg 47, D-89081 Ulm | P: +49 (0)731 140088-0 | F: +49 (0)731 140088-9000

E-Mail: info@aegid.de | www.aegid.de

AEG is a registered trademark used under license from AB Electrolux (publ).