



DATENBLATT | datasheet

Kompakt Lesegerät | Compact Reader ARE i2.0x LF

Elektrische Daten | electrical characteristics

Lesesystem reading systems	ASK, PSK, FSK
Betriebsfrequenz operational frequency	134,2 kHz
Schnittstelle interface	RS 232
Software software	Einfaches serielles ASCII Steuerprotokoll Easy serial ASCII based control protocol
Stromversorgung power supply	12V... 24V
Antennen antennae	Interne oder externe Luftspule oder Ferritspule Internal or external air core or ferrite core coil AAN Xi9F LF, AAN Xi9L LF

Umweltbedingungen | environment

Lagertemperatur storage temperature	-20°C bis up to +70°C
Betriebstemperatur operating temperature	-20°C bis up to +70°C
Gehäuse Schutzklasse packaging protection class	IP 65
Schock&Vibration Shock&Vibration	IEC 68-2-6 / 29

Befestigung | mounting option

2 Befestigungsstreben 2 mounting brackets	Hutschienemontage top hat rail mount
---	--

Abmessungen | dimension

Gewicht weight	Ca. 170 g
Länge length	90 mm
Breite width	58 mm
Höhe height	38 mm
Material material	PA6, ABS



AEG Identifikationssysteme GmbH

Hörvelsinger Weg 47, D-89081 Ulm | P: +49 (0)731 140088-0 | F: +49 (0)731 140088-9000

E-Mail: info@aegid.de | www.aegid.de

AEG is a registered trademark used under license from AB Electrolux (publ).